



SRK-ZM

Wall Mounted type



Standard equipment



FUNCTION



Comfortable Functions



Comfortable Air Flow Functions



Convenient & Economy Functions



Maintenance & Prevention Functions



Others



SPECIFICATIONS

Item	Model	SRK20ZM-S	SRK25ZM-S	SRK35ZM-S	SRK50ZM-S
Nominal cooling capacity	kW	2.0	2.5	3.5	5.0
Nominal heating capacity	kW	3.0	3.4	4.5	5.8
*Sound power level	Cooling	49	50	58	60
	Heating	52	55	59	61
*Sound pressure level	Cooling(Hi/Me/Lo)	33 / 27 / 21	34 / 28 / 21	42 / 32 / 22	46 / 37 / 26
	Heating(Hi/Me/Lo)	36 / 31 / 24	39 / 31 / 24	43 / 37 / 25	45 / 37 / 31
Air flow	Cooling(Hi/Me/Lo)	7.8 / 5.6 / 4.8	7.9 / 6.0 / 5.0	10.1 / 6.4 / 5.0	11.3 / 7.8 / 5.3
	Heating(Hi/Me/Lo)	9.8 / 6.3 / 5.0	10.6 / 6.5 / 5.1	12.8 / 9.4 / 6.1	13.5 / 10.2 / 7.5
Exterior dimensions (H×W×D)	mm	294×798×229			
Net weight	kg	9.5			
Ref. piping size	Liquid / Gas	6.35(1/4") / 9.52(3/8")			6.35(1/4") / 12.7(1/2")
Clean filter		Allergen Clear Filter × 1, Photocatalytic Washable Deodorizing Filter × 1			

The data are measured under the following conditions(ISO-T1). Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB. Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.
 * Indicates the value in an anechoic chamber. During operation these values are somewhat higher due to ambient conditions.

SRF-ZMX

Floor Standing type



Standard equipment



FUNCTION



Comfortable Functions



Comfortable Air Flow Functions



Convenient & Economy Functions



Maintenance & Prevention Functions



Others



SPECIFICATIONS

Item	Model	SRF25ZMX-S	SRF35ZMX-S	SRF50ZMX-S
Nominal cooling capacity	kW	2.5	3.5	5.0
Nominal heating capacity	kW	3.4	4.5	5.8
*Sound power level	Cooling	51	52	58
	Heating	51	52	58
*Sound pressure level	Cooling(Hi/Me/Lo/Ulo)	40 / 32 / 29 / 26	41 / 34 / 32 / 28	46 / 42 / 35 / 32
	Heating(Hi/Me/Lo/Ulo)	40 / 35 / 33 / 28	41 / 36 / 35 / 31	47 / 41 / 39 / 33
Air flow	Cooling(Hi/Me/Lo/Ulo)	9.0 / 7.6 / 6.7 / 5.8	9.2 / 7.8 / 7.3 / 6.4	11.5 / 9.6 / 7.4 / 6.6
	Heating(Hi/Me/Lo/Ulo)	10.5 / 8.2 / 7.7 / 6.6	10.7 / 8.3 / 8.1 / 7.4	12.0 / 10.0 / 9.4 / 7.6
Exterior dimensions (H×W×D)	mm	600×860×238		
Net weight	kg	18	19	
Ref. piping size	Liquid / Gas	6.35(1/4") / 9.52(3/8")		
Clean filter		Natural Enzyme Filter × 1 Photocatalytic Washable Deodorizing Filter × 1		

The data are measured under the following conditions(ISO-T1). Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB. Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.
 * Indicates the value in an anechoic chamber. During operation these values are somewhat higher due to ambient conditions.