



# In-line duct fans **SILENTUB-100**

**SILENTUB-100**



Transfer axial fan offering a very low noise level and specifically designed to work through a duct or to be flush mounted into the wall, ideal for ventilating small areas or to exchange heat between adjoining rooms. Fitted with single phase motors 230V-50Hz, IP44, Class II, with ball bearings for enhanced working life and assembled on silent-blocks.


## + Attributes



**Back draft shutter**  
SILENTUB-100 is fitted with an automatic back draft shutter to prevent air entry and limit heat leakage when the extractor is not operating.



**Silent-blocks**  
Motor mounted on silentelastastic block to absorb vibrations and reduce noise transmissions.



SILENTUB-100 can be flush mounted into the wall, ideal for ventilating small areas or to exchange heat between adjoining rooms.

## + Technical characteristics

Model	Speed (rpm)	Maximum absorbed power (W)	Ø duct (mm)	Air volume at free discharge (m <sup>3</sup> /h)	Sound pressure level* (dB(A))	Weight (kg)
SILENTUB-100	2450	12	100	100	37,5	0,5
SILENTUB-200	2350	16	120	190	42	0,7

\* Sound pressure level measured at 1,5 m, at the fan inlet, in free field.

## + Mounting Accessories



**Mounting foot  
PIE-100/120**  
Support for wall fixing  
(accessory)



**GSA-100**  
Flexible aluminium  
ducting.



**CX-80/125**  
Worm drive ducting  
clip.



**GR-100**  
Plastic exterior  
grille.



**PER-100W**  
Exterior back  
draft shutter.